


Technical data sheet

Manufacturer	AQUAFIDES	
UV Disinfectionsystem	Multi-lamp system	
Productfamily	COMPACT	
System type	4 AF300 T	

Irradiation chamber

Connection dimension	DN150 (6") PN 10/16	shape	U
Connectionsystem	Loose flange (EN 1092-1 type 02)	Material	
Vent valve and drainage square plug	G 1/2"	DIN EN 10088-3	1.4404
Sampling valve at inlet and outlet	G 1/4"	EN Material designation	X2CrNiMo17-12-2
Socket sensor connection system	COMPACT	AISI	316 L
Mounting thread	1"	B.S.	316S11
Irradiation chamber volume	83 l	Surface irradiation chamber	bath pickled
Weight without medium	58 kg	Design	Standard
Weight with medium	141 kg	Operating pressure (MOP)	PN 10/16 EN 13445-3
Protection class	IP65	Installation position	horizontal, vertical (any)
		Inlet/outlet distance	none
		Interior cleanable without disassembly	☉

Dimensions



Symbolic representation - No dimensional drawing

A - Length irradiation chamber	1134 mm	M1 - Maintenance area lamp	1250 mm
B - Centre distance inlet/outlet	918 mm	M2 - Maintenance area	200 mm
C - Centre distance to reactor outer edge	108 mm	M3 - Maintenance area sensor	200 mm
D - Connection dimension	DN150 (6")		
E - Sensor position	459 mm		
F - Outer diameter irradiation chamber	324 mm		
G - Width irradiation chamber	432 mm		
H - Total length	1203 mm		

Should the maintenance ranges be undershot, please contact AQUAFIDES.

UV lamp

Manufacturer	AQUAFIDES
Number of lamps	4
Lamp type	AF300A
Technology	Low pressure amalgam lamp
Amalgamposition	Spot
AF-No. lamps	A00300
Power consumption (per lamp, including electronic ballast)	270 W
UV lamp current (normal operation per lamp)	3,4 A

Dimmability and control mode	
Power controlled	●
Dimming range power	50
Current controlled	-
Guaranteed lamp service life	see GTC
Expected lamp service life	12000 h
Medium temperature	0 ... 70 °C

UV sensor system

Manufacturer	AQUAFIDES
UV sensor type	DigiNorm
Article no.	A30000
Number of UV sensors	1
Opening angle	160°
Version	ÖNORM M 5873-1:2020, DIN 19294-1:2020
Type-tested	●
Calibrated	●
Recalibrated	●

Recalibration period	1 Year
System structure	Bus RS485
Operating mode	digital
UV Measuring range	2 ... 500 W/m²
Standard signal output (switchable)	0/4 ... 20 mA
Measuring accuracy	± 2 %
Selectivity - λ_{254}	≥ 99 %
Temperature stability	0 ... 75 °C

Device cable


Cable type	Lamp cable
Article no.	A70021

Cable type	UV sensor cable
Article no.	A70011

Protection class (mounted)	IP68
Cable length	9 m

Protection class (mounted)	IP68
Cable length	10,5 m

Control cabinet



Symbolic representation - No dimensional drawing

Type	Wallmount enclosures	Installation conditions ²
Height	700 mm	Ambient temperature of control cabinet +1°C ... +35°C
Width	500 mm	Ambient temperature Storage -20°C ... +60 °C
Depth	260 mm	Humidity max. 95%
Weight	0 kg	Outdoor installation -
Material	Coated sheet steel	Protection class IP54
Surface colour	RAL7035 Light gray	Thermal management Active ventilation
Surface structure	Structured powder coating	

² For details, please refer to the "General installation and operating instructions" (6.2 Permissible ambient conditions).

Electrical specifications

Operating voltage	210 ... 250 V/AC	External fuse protection	D16
Mains frequency	50 ... 60 Hz	Power factor (normal operation)	0,99 cos ϕ
Maximum connected load	1090 W	EMC tested	●
Nominal connected load	-	Safe to touch	●
Power consumption	4,9 A	Connection cable	
Operating connection	L/N/PE	Length	on site
Internal fuse portection	1x D13, 1x C6	Connector plug	-

19IO20221647 # MM # V3.7 # TDS_VI